

WATER BLASTING TRUCKS
FROM 24 GPM (600HP) - 5.2 GPM (125 HP)

**STRIPE
HOG
SH15**



**STRIPE
HOG
SH8000**



**STRIPE
HOG
SK5.2**



**TRIPLE
SPRAY
BAR**



3x 16" Spray Bars (48")

PTO AND AUXILIARY ENGINE DRIVEN - AVAILABLE ON THE CHASSIS OF YOUR CHOICE

SURFACE CLEANING TRUCKS

**SURFACE
HOG**



SURFACE HOG SPECIFICATIONS

Operating Pressure:	7,250 psi
Flow Rate:	7.9 gpm
Fresh Water Capacity:	610 gal.
Debris Water Capacity:	132 gal.
Blasting Width:	36"

**COMBINES DIAMOND CUTTING TEETH
AND WATER BLASTING**

**HOG
TUSK**



PCD TEETH OPTIONS



PCD teeth + 40K psi nozzles

Grind Only | Water Blast Only

Grind + Water Blast together

Uses half the water

Removes markings 2x faster

Only available on new HOGs



GRINDING & GROOVING TRUCKS

**GRINDER
HOG**



3/4-HEAD GRINDER HOG SPECIFICATIONS

Cutting Width:	Up to 13" (36" w/Extension)
Cutting Heads:	3 or 4
Vacuum Recovery:	4,400 - 6,600 CFM
Debris Tank Capacity:	6 Cubic Yards (usable)
Water Tank Capacity:	1,000 gal
Low Speed Control:	Up to 8 MPH

**GRINDER
HOG
GH2**



NO CDL REQUIRED

2-HEAD GRINDER HOG SPECIFICATIONS

Cutting Width:	Up to 13" (36" w/Extension)
Cutting Heads:	2
Vacuum Recovery:	2,200 CFM
Debris Tank:	4 Cubic Yards (usable)
Low Speed Control:	Up to 6 MPH

RUMBLE & BROOM TRUCKS

**RUMBLE
HOG**



RUMBLE HOG SPECIFICATIONS

Cutting Width:	Up to 20"
Grinding Speed:	Up to 5 MPH
Grooving Speed:	Up to 3.5 MPH
Rumble Strip Cutting Speed:	Up to 5 MPH
Water Tank Capacity:	900 gal
Debris Tank Capacity:	4 Cubic Yards (usable)

**BROOM
HOG**



NO CDL REQUIRED

BROOM HOG SPECIFICATIONS

Broom Width:	32"
Broom Reach:	12" beyond each tire
Production Rate:	20+ Cubic Yards per hour
Auxiliary Engine:	140 HP Diesel
Water Tank:	400 gal.

**THERMO TRUCKS
FROM 16,000 LBS. - 4,000 LBS.**

**THERMO
HOG**



THERMO HOG SPECIFICATIONS

Kettle Capacity:	4,000 lbs. - 16,000 lbs.
Melt Rate:	8,000 lbs./hr - 24,000 lbs./hr
Bead Tank Capacity:	3,000 lbs. - 8,000 lbs.
Speed Control:	2-10 MPH
Burner:	1.2 - 1.4 million BTU
Operation:	1hr start-up/instant shutdown

**EPOXY/POLYUREA TRUCKS
EPOXY HOG
NON-CDL MODEL AVAILABLE**



EPOXY HOG SPECIFICATIONS

Material Tanks:	From 325 gal per component 1 Glycol Pump vs 5 to 6
Bead Tank Capacity:	6,000 lbs.
Air Compressor:	250 CFM
# of Burners:	1 vs 4 or 5
High-Power Pumps:	Inline legs for easy access Air-driven. VERY SIMPLE

SPEED CONTROL AND HOG TOOLS COME STANDARD ON EVERY MODEL

**MINI
HOG**



MINI HOG SPECIFICATIONS - MELTS ITS OWN THERMO

Models:	400lbs	Thermo or 3M Tape
Kettle Sizes:	400-600 lbs.	
Engine:	25HP Propane	
Thermo Shoe:	4", 6", 8", 12" Standard	Customization Available
Air Compressor:	8.5 CFM at 125 psi	

**THERMO
PRE-MELTER**



THERMO PRE-MELTER

Available Models:	TPM 6, TPM 4 Hauler, TPM 4 Hauler RPM, TPM 8 Hauler
Kettle Capacity:	2,000 - 3,000 lbs.
Burner:	1 Million BTU, 24"
Operation:	< 1hr start-up/instant shutdown
Kettles:	Lateral: Loads at your feet

Lateral design only available from HOG



Our Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators minimize cost, maximize productivity, and optimize results.



START LEARNING TODAY

**TOTAL PAVEMENT
SOLUTIONS**

- PAVEMENT MARKING & RUBBER REMOVAL
- PAVEMENT MARKING
- SURFACE CLEANING / PREPARATION
- SURFACE RETEXTURING
- GRINDING, GROOVING, RUMBLING


HOG
TECHNOLOGIES

www.TheHog.com



USA Office
3920 SE Commerce Ave.
Stuart, FL 34997
1-772-214-1714

European Office
Vavreckova 7074
760 01 Zlin, Czech Republic
+420 573 903 031