

GRINDER HOG



**SINGLE OPERATOR
RUN UP TO 4 CUTTER HEADS AT ONCE
COMPUTER-CONTROLLED VACUUM SYSTEM CLEANS WHILE WORKING
HIGH DUMP SYSTEM TO OFFLOAD DEBRIS INTO DUMP TRUCK**




GRINDING



GROOVING



REFLECTOR CUT



**SINUSOIDAL
RUMBLES**





GRINDER HOG GH3|GH4

GRINDING, GROOVING, RUMBLING

ADVANTAGES

The Grinder Hog features grinder heads on each side of the truck that are capable of extending outward up to 36" (91.44 cm) from the chassis. The Grinder Hog can be configured with 3 or 4 grinding heads. The grinder head supports a variety of PCD grinding teeth for different finish profiles.

With our Low-Speed Control, the Grinder Hog can grind at speeds up to 8 MPH (12.87 KM/H). The Grinder Hog comes with a computer controlled profiling (or CCP) package for on-the-fly adjustment of your skip line or recessed pavement markers. CCP makes it possible for one operator to control up to 4 heads at once.

The simultaneous vacuum recovery system of the Grinder Hog utilizes two or three 2,200 CFM positive displacement blowers, and pollution control technology (PCT) to control noise and dust. The debris is then stored in a debris tank that can hold 6 cubic yards.

The Grinder Hog comes standard with a scissor lift high dump, allowing you to raise and tilt the debris tank at a 47° angle for easy dumping of debris. The Grinder Hog also comes with a 1,000 gal (3,785 liters) water tank that can be filled with fresh, potable water for use in the PCT system while grinding, keeping the machine compliant with Airborne Silica guidelines set forth by the EPA.

THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University - Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

SPECIFICATIONS

GRINDING HEADS: 3 or 4

CUTTING WIDTHS: Up to 18" (45.7 cm) - 13" (33 cm) Standard

HEAD EXTENSION: Up to 36" (91.44 cm) away from chassis

VACUUM (3 HEADS): 2x 2,200 CFM 8" (20.32 cm) Blowers

VACUUM (4 HEADS): 3x 2,200 CFM 8" (20.32 cm) Blowers

WATER CAPACITY: 1,000 gallons (3,785 liters)

DEBRIS CAPACITY: 6 cubic yards usable

LOW SPEED CONTROL: Up to 8 MPH (12.87 KM/H)

CUTTING TEETH OPTIONS:



FLAT



ROUND



DOUBLE ROUND



TRIPLE ROUND

OPTIONS



18" CUTTER DRUM

