

STRIPE HOG SH24




**ROAD
RETEXTURING**




**SURFACE
PREPARATION**




**RUNWAY
RUBBER
REMOVAL**



**AIRPORT
APRON
CLEANING**



**PAINT
CLEANING &
REJUVENATION**



**HYDRAULIC
SPILL CLEANUP**





STRIPE HOG SH24

RUBBER AND PAINT REMOVAL

ADVANTAGES

The Stripe Hog SH24 is a water blasting and recovery system designed for either asphalt or concrete roadways and airfields. The Stripe Hog SH24 can prepare to vacate the runway in under 1 minute.

The SH24 is equipped with two Jetstream pumps that produce ultra-high pressure needle-sharp water blasting jets up to 40,000 psi (2,750 bar) and up to 24 gpm (91 lpm). It uses ordinary fresh water without chemicals or detergents, along with a vacuum recovery system that is twice as powerful as the SH8000.

With up to five 1,050 gallon (3,974 liters) water tanks and an 1,800 gallon (6,813 liters) debris tank, the SH24 can stay on the job for several hours before dumping or replenishing water. An easy-to-use dump system and a remote-control panel in the cab make this truck a one-person operation...saving both time and money.

Separating water from solids our dewatering system filters the reclaimed water up to 100 micron for safe and easy disposal of the solid debris.

The SH24 comes with up to three 48" (121.92 cm) heads (that contain three 16" (40.64 cm) spray bars) supported by a 5-axis arm (two 48" heads) or a 7-axis arm (three 48" heads). The outer nozzles of each 16" (40.64 cm) spray bar contains a fan nozzle. This eliminates the gap when turning with the heads, ensuring full cleaning coverage with the head. HOG Tusk is not supported when using three 48's triple heads.

Our optional patented bladder tanks allow you to carry both fresh water and debris water in the same footprint allowing you to use the debris collection box for dewatered solid material only, radically increasing up time.

THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University - Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

SPECIFICATIONS

OPERATING PRESSURE: 40,000 PSI (2,750 BAR)

FLOW RATE: 24 GPM (91.1 LPM)

BLASTING WIDTHS: 96"-144" (244-365 cm)

WATER CAPACITY: Up to 5x 1,050 gallons (3,974 liters)

DEBRIS CAPACITY: 1,800 gallons (6,813 liters), Up to 7,050 gallons (26,687 liters) with optional bladder bags.

VACUUM: 4" @ 750 CFM

RUBBER REMOVAL RATE: 60,000 sq. ft/hr (5,574 m²/hr)

OPTIONS




48" TRIPLE HEAD



GROUND HOG



BLADDER TANKS



HOG TUSK

