

# STRIPE HOG SH7500



MARKING  
REMOVAL



SURFACE  
PREPARATION



RUNWAY  
RUBBER  
REMOVAL



CURING  
COMPOUND  
REMOVAL



ROAD  
RETEXTURING



AIRPORT  
APRON  
CLEANING



PAINT  
CLEANING &  
REJUVENATION



HYDRAULIC  
SPILL CLEANUP



**HOG**



# STRIPE HOG SH7500

RUBBER AND PAINT REMOVAL

## ADVANTAGES

The Stripe Hog™ SH7500 is a water blasting and recovery system designed for either asphalt or concrete roadways and airfields. The Stripe Hog SH7500 can prepare to vacate the runway in under 1 minute.

The SH7500 is equipped with ultra-high pressure needle sharp water blasting jets creating up to 40,000 psi (2,750 bar) and up to 9 gpm (34.1 lpm). It uses ordinary fresh water without chemicals or detergents, along with a vacuum recovery system.

With a large water and debris tank capacity the SH7500 can stay on the job for several hours before dumping or replenishing with fresh water. An easy-to-use dump system and a remote-control panel in the cab make this truck a one-person operation...saving both time and money.

Separating water from solids our dewatering system filters the reclaimed water up to 100 micron for safe and easy disposal of the solid debris.

The Stripe HOG SH7500 is HOG Tusk compatible. The HOG Tusk is a single head that contains PCD grinding teeth and 40,000 PSI water jet nozzles. The HOG Tusk can grind only, water blast only, or perform both functions simultaneously, allowing you to remove markings at twice the speed using only half of the required water.

Our patented bladder tanks allow you to carry both fresh water and debris water in the same footprint allowing you to use the debris collection box for dewatered solid material only, radically increasing up time. The Stripe Hog™ SH7500 is built on a Mack GU432 chassis domestically.

## SPECIFICATIONS

**OPERATING PRESSURE:** 40,000 PSI (2,750 BAR)

**FLOW RATE:** 9 GPM (34.1 LPM)

**BLASTING WIDTHS:** 6"-48" (15.2-121.92 cm) Standard as a single head

**WATER CAPACITY:** 1,200 gallons (4,542 liters)

**DEBRIS CAPACITY:** 750 gallons (2,839 liters), 1,950 gallons with optional bladder bags.

**VACUUM:** 4" @ 750 CFM or 6" blowers @ 1,400 CFM

**RUBBER REMOVAL RATE:** 30,000 sq. ft/hr (2,787 m<sup>2</sup>/hr)

**MARKING REMOVAL RATE:** 5,557 linear ft/hr (1,693 linear meters/hr)

## OPTIONS



HOG RIDER

GROUND HOG



HOG TUSK

36"/48" TRIPLE HEAD



BLADDER TANKS



24" TWIN HEAD

## THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University – Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

**USA:** 3920 SE Commerce ave., Stuart, FL 34997 • **PHONE:** 1-772-214-1714

**EUROPE:** Vavreckova 7074 | 760 01 Zlin, Czech Republic • **PHONE:** +420 573 903 031

**EMAIL:** sales@thehog.com • **WEB:** www.TheHog.com

