

STRIPE HOG SH8000



MARKING
REMOVAL



SURFACE
PREPARATION



RUNWAY
RUBBER
REMOVAL



CURING
COMPOUND
REMOVAL



HYDRAULIC
SPILL CLEANUP



ROAD
RETEXTURING



AIRPORT
APRON
CLEANING



PAINT
CLEANING &
REJUVENATION



BARRIER WALL
CLEANING



HOG



STRIPE HOG SH8000

RUBBER AND PAINT REMOVAL

ADVANTAGES

The Stripe Hog™ SH8000 is a water blasting and recovery system designed for either asphalt or concrete roadways and airfields. The Stripe Hog SH8000 can prepare to vacate the runway in under 1 minute.

The SH8000 is equipped with ultra-high pressure needle sharp water blasting jets creating from 1,000 psi (69 bar) to 40,000 psi (2,750 bar) and up to 12 gpm (45.4 lpm). It uses ordinary fresh water without chemicals or detergents, along with a vacuum recovery.

Separating water from solids our dewatering system filters the reclaimed water up to 100 micron for safe and easy disposal of the solid debris.

With a large water and debris tank capacity the SH8000 can stay on the job for several hours before dumping or replenishing with fresh water. An easy-to-use dump system and a remote-control panel in the cab make this truck a one-person operation...saving both time and money.

The Stripe HOG SH8000 is HOG Tusk compatible. The HOG Tusk is a single head that contains PCD grinding teeth and 40,000 PSI water jet nozzles. The HOG Tusk can grind only, water blast only, or perform both functions simultaneously, allowing you to remove markings at twice the speed using only half of the required water.

Our optional patented bladder tanks allow you to carry both fresh water and debris water in the same footprint allowing you to use the debris collection box for dewatered solid material only, radically increasing up time. The Stripe Hog™ SH8000 can be built on various domestic and international truck chassis to meet the road worthiness criteria in your area.

THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University – Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

SPECIFICATIONS

OPERATING PRESSURE: 40,000 PSI (2,750 BAR)

FLOW RATE: 12 GPM (45.5 LPM)

BLASTING WIDTHS: 6"-48" (15.2-121.92 cm)

WATER CAPACITY: 3,150 gallons (11,924 liters)

DEBRIS CAPACITY: 1,800 gallons (6,813 liters), 4,950 gallons (18,737 liters) with optional bladder bags.

VACUUM: 6" @ 1,400 CFM or 8" @ 2,350 CFM

RUBBER REMOVAL RATE: 40,000 sq. ft/hr (3,716 m²/hr)


MARKING REMOVAL RATE: 6,500 linear ft/hr (1,981 linear meters/hr)

OPTIONS



HOG RIDER

GROUND HOG



HOG TUSK



36"/48" TRIPLE HEAD
24" TWIN HEAD



HIGH DUMP



HOG TRACKS

USA: 3920 SE Commerce ave., Stuart, FL 34997 • **PHONE:** 1-772-214-1714

EUROPE: Vavreckova 7074 | 760 01 Zlin, Czech Republic • **PHONE:** +420 573 903 031

EMAIL: sales@thehog.com • **WEB:** www.TheHog.com

