

# GROUND HOG

HT1000SR



**THE WORLD'S ONLY SELF-ROTATED DEVICE  
WITH RPM CONTROL**





# GROUND HOG HT1000SR

RUBBER AND PAINT REMOVAL

## ADVANTAGES

The Ground Hog™ HT1000SR is a lightweight, easy-to-transport tool that easily connects to any 40,000 psi (2,750 bar) pump.

The Ground Hog is configured with a 14" (35.5 cm) blasting head using a 15-nozzle spray bar configuration. It is capable of cleaning 500 - 1,500 square feet/hr (46.5 - 139.4 square meters/hr) with simultaneous vacuum recovery (requires 800 cfm.)

With the self-rotating Ground Hog, there is no potential for imbalance.

The self-rotating Ground Hog does not require hydraulic, electrical, or pneumatic power to operate. The speed of the self-rotating spray bar can be controlled via a knob with a maximum speed of 2,500 RPMs.

## SPECIFICATIONS

**PRESSURE:** 40,000 psi (2,750 bar)

**FLOW RATE:** 9 GPM (34.1 LPM)

**BLASTING WIDTH:** 14" (35.5 cm)

**VACUUM RECOVERY:** Requires 800 cfm minimum

**WEIGHT:** 105 lbs. (47.6 kg)

**MAX ROTATION:** 2,500 RPM

## THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University - Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

