

PAINT HOG JR



ATOMIZED AIR





PAINT HOG JR

PAVEMENT MARKING EQUIPMENT

ADVANTAGES

The Paint HOG Jr is built on a 2023 Isuzu NRR chassis and does NOT require a CDL license to operate.

The Paint HOG Jr features two 80-gallon (303-liter) SS pressurized lateral kettles under the deck, allowing more storage space for material. The material is gravity fed from two paint totes into the kettles removing the need to stop and remove the totes if the kettles are full.

The aluminum-constructed canopy covers the deck which features a rear step with an RPM basket option, D-rings for machine mounting (such as bitumen hardline). The regulator panel is mounted to the canopy for deck space.

The Paint HOG Jr uses two 49 GPM (185 LPM) SS diaphragm pumps for paint recirculation. This also achieves flow mixing of the tank.

SPECIFICATIONS

PAINT TANKS: 2x 80 gallons (303 liters)

BEAD TANKS: 2x 500 lbs. (226 kg) w/ 1,000 lbs. (453 kg) reserve

COMPRESSOR: 115 cfm @ 100 PSI (6.89 bar)

WATER TANK: 40 gallons (151 liters)

PAINT TOTES: 2

HYDRAULICS: Compressor-driven

PUMPS: 2x 49 GPM (185 LPM)

THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University - Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

USA: 3920 SE Commerce ave., Stuart, FL 34997 • **PHONE:** 1-772-214-1714

EUROPE: Vavreckova 7074 | 760 01 Zlin, Czech Republic • **PHONE:** +420 573 903 031

EMAIL: sales@thehog.com • **WEB:** www.TheHog.com