RUMBLE



NO TRAILER REQUIRED

3-IN-1 MACHINE: CUT ANY TYPE OF RUMBLE , RPM PROFILE, GRIND OR GROOVE











RUMBLING





RUMBLE HOG GRINDING, GROOVING, RUMBLING

ADVANTAGES

The Rumble Hog is a 3-in-1 multi-purpose machine. It can grind to remove pavement markings, groove for in-laid pavement markings and cut all types of rumble strips.

The Rumble Hog is capable of customized rumble strip cutting patterns. Cutting is both mechanically and electronically synchronized with the truck's forward movement. It can reach a maximum speed of 5 mph (8 kmh).

Computer Controlled Profiling is included and provides the ability to perform sinusoidal rumble cuts, plunge cuts, and recessed marker profiles. These profiles can be customized to any specification.

The rear-mounted drum is capable of shifting from one side of the truck to the other by use of a simple joystick control located in the cab. The Rumble Hog includes a bumper extension that allows the cutter drum to extend an additional 12" (30.5 cm) past either side of the truck. This allows the operator to keep the truck centered in its lane while making cuts to the center or edge lines on the road. Only one extension is needed as it can be deployed on either side of the truck. It is easily removed and reset using two pins.

The Mack Granite chassis provides power and torque and holds a large capacity water tank for dust suppression. Dumping can be accomplished either on the job site or maintained in the built-in debris bin for disposal at an off-site location of choice.

THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

SPECIFICATIONS

TEETH: PCD

WATER CAPACITY: 900 gal (3,407 liters) for dust suppression DEBRIS CAPACITY: 4 cubic yards (usable) GRINDING RATE: Up to 5 MPH (8 KM/H) GROOVING RATE: Up to 3.5 MPH (5.6 KM/H) RUMBLE STRIPS: Up to 5 MPH (8 KM/H) SINUSOIDAL RATE: 1 MPH (12" centers), 1.5 MPH (16" centers)

CUTTING TEETH OPTIONS:



FLAT



ROUND (FLAT & DOMED)

DOUBLE ROUND (DOMED ONLY)

OPTIONS





HIGH DUMP

VACUUM



