

STRIPE HOG SK2000



**MARKING
REMOVAL**




**SURFACE
PREPARATION**



**RUNWAY
RUBBER
REMOVAL**




**CURING
COMPOUND
REMOVAL**



**ROAD
RETEXTURING**



**AIRPORT
APRON
CLEANING**



**PAINT
CLEANING &
REJUVENATION**



**HYDRAULIC
SPILL CLEANUP**



HOG



STRIPE HOG SK2000

RUBBER AND PAINT REMOVAL

ADVANTAGES

The Stripe Hog™ SK2000 is an auxiliary-driven water blasting and recovery system designed for either asphalt or concrete roadways and airfields. The Stripe Hog SK2000 can prepare to vacate the runway in under 1 minute.

The SK2000 is equipped with ultra-high pressure needle sharp water blasting jets creating up to 40,000 psi (2,750 bar) and up to 7.6 gpm (28.7 lpm). It uses ordinary fresh water without chemicals or detergents, along with a vacuum recovery system. Separating water from solids, it processes the reclaimed water for safe and easy disposal of the solid debris.

With a large water and debris tank capacity the SK2000 can stay on the job for several hours before dumping or replenishing with fresh water. An easy-to-use dump system and a remote-control panel in the cab make this truck a one-person operation... saving both time and money.

Our dewatering system filters the reclaimed water up to 100 micron for safe and easy disposal of the solid debris.

Our patented bladder tanks allow you to carry both fresh water and debris water in the same footprint allowing you to use the debris collection box for dewatered solid material only, radically increasing up time. The Stripe Hog™ SK2000 is built on an Isuzu FTR chassis; however, it can be mounted to the chassis of your choice. The SK2000 is also available as a trailer-mounted system.

THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University - Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

SPECIFICATIONS

OPERATING PRESSURE: 40,000 PSI (2,750 BAR)

FLOW RATE: 7.6 GPM (28.7 LPM)

BLASTING WIDTHS: 6"-48" (15.2-121.92 cm) Standard as a single head

WATER CAPACITY: Up to two 600 gallons (2,271 liters) depending on the chassis

DEBRIS CAPACITY: 750 gallons (2,839 liters)

VACUUM: 4" @ 750 GFM & 6" @ 1,400 CGM

RUBBER REMOVAL RATE: 32,000 sq. ft/hr (3,000 m2/hr)

MARKING REMOVAL RATE: 12,000 linear ft/hr (3,657 linear meters/hr)

OPTIONS




HOG RIDER




GROUND HOG



MOUNT TO TRAILER



36"/>" TRIPLE HEAD
24" TWIN HEAD



HOG TUSK

USA: 3920 SE Commerce ave., Stuart, FL 34997 • PHONE: 1-772-214-1714

EUROPE: Vavreckova 7074 | 760 01 Zlin, Czech Republic • PHONE: +420 573 903 031

EMAIL: sales@thehog.com • WEB: www.TheHog.com

