



MARKING REMOVAL



SURFACE PREPARATION



RUNWAY RUBBER REMOVAL



CURING COMPOUND REMOVAL



ROAD RETEXTURING



AIRPORT APRON CLEANING



PAINT CLEANING & REJUVENATION



HYDRAULIC SPILL CLEANUP





STRIPE HOG SK7500

RUBBER AND PAINT REMOVAL

ADVANTAGES

The Stripe Hog™ SK7500 is an auxiliary engine-driven water blasting and recovery system designed for either asphalt or concrete roadways and airfields The Stripe Hog SK7500 can prepare to vacate the runway in under 1 minute.

The SK7500 is equipped with ultra-high pressure needle sharp water blasting jets creating up to 40,000 psi (2,750 bar) and your choice of a 7.8 GPM (29.5 LPM) or 9.8 gpm (37 lpm) pump. It uses ordinary fresh water without chemicals or detergents, along with a vacuum recovery system. Separating water from solids, it processes the reclaimed water for safe and easy disposal of the solid debris.

With a large water and debris tank capacity the SK7500 can stay on the job for several hours before dumping or replenishing with fresh water. An easy-to-use dump system and a remote-control panel in the cab make this truck a one-person operation...saving both time and money.

Our dewatering system filters the reclaimed water up to 100 micron for safe and easy disposal of the solid debris.

Our patented bladder tanks allow you to carry both fresh water and debris water in the same footprint allowing you to use the debris collection box for dewatered solid material only, radically increasing up time.

THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University Our New Learning Management
 System is the perfect place for your team members to
 receive certification and on-going training. Certified
 Operators maximize the productivity of your truck while
 maintaining the highest levels of safety at the lowest
 operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

SPECIFICATIONS

OPERATING PRESSURE: 40,000 PSI (2,750 BAR) **FLOW RATE:** 7.8 GPM (29.5 LPM) or 9.8 GPM (37 LPM) **BLASTING WIDTHS:** 6"-24" (15.2-60.96 cm) Standard as a

single head

WATER CAPACITY: 1,200 gallons (4,542 liters)

DEBRIS CAPACITY: 750 gallons (2,839 liters), 1,950 gallons with

optional bladder bags.

VACUUM: 4" @ 750 CFM (7.8 GPM Pump) or 6" 1,400 CFM (9.8

GPM Pump)

OPTIONS





HOG RIDER

GROUND HOG





24" TWIN HEAD

48" TRIPLE HEAD



BLADDER TANKS

USA: 3920 SE Commerce ave., Stuart, FL 34997 • **PHONE:** 1-772-214-1714 **EUROPE:** Vavreckova 7074 | 760 01 Zlin, Czech Republic • **PHONE:** +420 573 903 031 **EMAIL:** sales@thehog.com • **WEB:** www.TheHog.com

