

GRINDER HOG



**SINGLE OPERATOR
RUN UP TO 4 CUTTER HEADS AT ONCE
COMPUTER-CONTROLLED PROFILING FOR ANY PATTERN
AUTO-CLEANS WHILE WORKING
HIGH DUMP SYSTEM TO OFFLOAD DEBRIS INTO DUMP TRUCK**




GRINDING



GROOVING



REFLECTOR CUT



**SINUSOIDAL
RUMBLES**



**LIMITED TRADITIONAL
RUMBLES**



HOG



GRINDER HOG GH4

GRINDING, GROOVING, RUMBLING

ADVANTAGES

The Grinder HOG GH4 features (2) grinder heads on each side of the truck that are capable of extending outward up to 36" (91.44 cm) from the chassis. The grinder heads have easy accessible grinding drums that support a variety of PCD grinding teeth for different finish profiles and can be fitted with Diamond Saw Blades when local specs require.

Its Low-Speed Control system, allows the Grinder HOG GH4 to operate at any speed up to 8 MPH (12.87 KM/H). The Grinder HOG GH4 is equipped with our Computer Controlled Profiling ("CCP") package for on-the-fly adjustment of the grind profile or recessed pavement marker cuts. CCP also makes it possible for a single operator to control up all (4) heads independently or at once from the safety of the cab.

Best-in-class vacuum recovery is achieved through its reinvented Blower System featuring (3) 2,200 CFM Positive Displacement Rotary Style blowers, new silencer technology for noise reduction, and filter socks with auto-clean technology for Dust control and vacuum efficiency.

Recovered debris is stored in a Rear-Dumping High-Lift tank with an industry leading 7 cubic yards of usable space that can be deposited to the ground or a receiving container including most Dump Trucks.

THE HOG DIFFERENCE

- 98% of spare parts orders are shipped on the same day they are received, resulting in minimal downtime.
- Hog Tech University – Our New Learning Management System is the perfect place for your team members to receive certification and on-going training. Certified Operators maximize the productivity of your truck while maintaining the highest levels of safety at the lowest operating costs.
- Hog Technologies has a team of engineers and over 100 years of combined real-world experience to create the world's best solutions in every product we manufacture.
- 24/7/365 customer support is available with Certified Technicians within 10 minutes in multiple languages.

SPECIFICATIONS

GRINDING HEADS: 4

CUTTING WIDTHS: Up to 18" (45.7 cm) - 13" (33 cm) Standard

HEAD EXTENSION: Up to 36" (91.44 cm) away from chassis

VACUUM: 3x 2,200 CFM 8" (20.32 cm) Blowers

WATER CAPACITY: 150 gallons (567 liters)

DEBRIS CAPACITY: 7 cubic yards usable

LOW SPEED CONTROL: Up to 8 MPH (12.87 KM/H)

CUTTING TEETH OPTIONS:



FLAT



ROUND




DOUBLE ROUND



DIAMOND SAWS


OPTIONS



18" CUTTER DRUM



CANOPY ENCLOSURE



OPERATOR STATION



EXTRA MONITORS,
CAMERAS, 360 SYSTEM

LONG STROKE CYLINDERS

Allows for special H-Frame marker cuts.

MAGNETIC SENSORS

Automated metal avoidance to lift heads and protect equipment.

